Windows®. Life without Walls™. Fujitsu recommends Windows 7.



DATA SHEET

FUJITSU ESPRIMO E3721 E-STAR 5.0 DESKTOP PC

YOUR FLEXIBLE ECONOMY PC

ESPRIMO E3721 E-STAR 5.0

The ESPRIMO E3721 E-Star 5.0 is the ideal choice for large enterprise customers who are looking for the latest Intel® Core™ i technology. This small form factor PC, less than 13 litres in volume, combines top performance and extremely attractive prices. Equipped with a power supply unit with up to 87% efficiency and selected components it complies with the ENERGY STAR® standard, thus saving energy and protecting the environment. Freely configurable, with the latest technology and an extended product lifecycle of up to 12 months, this PC is the perfect choice for cost-driven projects.



INTELLIGENT PERFORMANCE AND BEST PRICE/PERFORMANCE RATIO

Cost-effective system for large enterprise projects

■ State-of-the-art Intel® CoreTM processors with Turbo Boost and hyperthreading technology

FLEXIBILITY

Freedom of choice with tailored systems, perfect fit for specific requirements

■ Flexible logistic concept - customizing program (made4you)

RELIABLILITY

Excellent quality and functional stability

■ Proprietary development and production in Europe

LIFECYCLE

Hardware continuity for long lasting project needs

■ Managed lifecycle up to 12 months

MEETS ENERGY STAR® 5.0 AND BLUE ANGEL REQUIREMENTS

Low power consumption and low costs, without any loss in performance.

■ Power supply with up to 87% efficiency.











COMPONENTS

PROCESSOR	Intel® Core™ i7-870 processor (4 Cores / 8 Threads, 2.93 GHz, 8 MB)
	Intel® Core™ i7-860 processor (4 Cores / 8 Threads, 2.80 GHz, 8 MB)
	Intel® Core™ i5-760 processor (4 Cores / 4 Threads, 2.80 GHz, 8 MB)
	Intel® Core™ i5-680 processor (2 Cores / 4 Threads, 3.6 GHz, 4 MB, Intel® HD Graphics)
	Intel® Core™ i5-660 processor (2 Cores / 4 Threads, 3.33 GHz, 4 MB, Intel® HD Graphics)
	Intel® Core™ i5-650 processor (2 Cores / 4 Threads, 3.20 GHz, 4 MB, Intel® HD Graphics)
	Intel® Core™ i3-550 processor (2 Cores / 4 Threads, 3.20 GHz, 4 MB, Intel® HD Graphics)
	Intel® Core™ i3-540 processor (2 Cores / 4 Threads, 3.06 GHz, 4 MB, Intel® HD Graphics)
	Intel® Pentium® processor G6950 (2 Cores / 2 Threads, 2.80 GHz, 3 MB, Intel® HD Graphics)
OPERATING SYSTEM	
	Genuine Windows® 7 Home Basic (EM) 32-bit
operating eyetem optional promotance	Genuine Windows® 7 Home Premium 64-bit
	Genuine Windows® 7 Professional 32-bit
	Genuine Windows® 7 Professional 64-bit
Operating system compatible	openSUSE Linux
	Genuine Windows Vista®
O	Genuine Windows® XP
Operating system notes	Dependent on configuration Windows 7 [®] versions are: Microsoft Office 2007 ready
	Microsoft Office 2010 preloaded. Purchase a Product Key to activate a full Microsoft Office 2010 suite.
	Limited Windows XP support. Microsoft discontinued Windows XP certification on system level.
MEMORY MODULES	2 GB (1 module(s) 2 GB) DDR3, unbuffered, non-ECC, 1333 MHz, PC3-10600, DIMM
	4 GB (1 module(s) 4 GB) DDR3, unbuffered, non-ECC, 1333 MHz, PC3-10600, DIMM
HARD DISK DRIVES (INTERNAL)	SSD SATA, 128 GB, 2.5-inch
HAND DISK DRIVES (INTERNAL)	SATA, 120 db, 2.3-11011 SATA II, 7200 rpm, 1000 GB, 3.5-inch, S.M.A.R.T.
	SATA II, 7200 rpm, 500 GB, 3.5-inch, S.M.A.R.T.
	SATA II, 7200 rpm, 320 GB, 3.5-inch, S.M.A.R.T.
	SATA II, 7200 rpm, 250 GB, 3.5-inch, S.M.A.R.T.
	SATA II, 7200 rpm, 160 GB, 2.5-inch, S.M.A.R.T.
Hard disk notes	Supporting NCQ and 3 GBit
GRAPHICS ADD ON CARDS (OPTIONAL)	DP to DVI-D (single link) Adapter Cable
	NVIDIA® GeForce® 9300GE display port low profile, 512 MB
	NVIDIA® Quadro® NVS 290 low profile, 256 MB
DRIVES (OPTIONAL)	Blu-ray Disc™ Triple Writer
	DVD-ROM
	DVD Super Multi
	MultiCard Reader 20in1, 3.5-Inch
INTERFACE ADD ON CARDS/COMPO-	
NENTS (OPTIONAL)	
•	WLAN III, 802.11g/Draft-n (Windows only)
	Parallel Interface
	eSATA Interface
	Dual serial card PCI LP
Base unit	ESPRIMO E3721 E-Star5
MAINBOARD	
Mainboard type	D2942
Formfactor	μΑΤΧ
Chipset	Intel® H55
Processor socket	LGA 1156
	2500

Windows®. Life without Walls $^{\text{TM}}$. Fujitsu recommends Windows 7.

MAINBOARD	
Processor quantity maximum	1
Memory slots	4 DIMM (DDR3)
Supported capacity RAM (max.)	16 GB
Memory frequency	1333 MHz
Memory notes	Dual channel support.
	For dual channel performance, 2 memory modules have to be ordered. Capacity per channel has to be the same.
LAN	10/100/1000 MBit/s Broadcom BCM57780
BIOS version	Phoenix 6.0
BIOS features	BIOS Flash EPROM update by software Recovery BIOS
Audio codec	Realtek ALC663
Audio features	High Definition audio, 5.1 surround sound
I/O CONTROLLER ON BOARD	
Serial ATA total	4
Controller functions	Serial ATA II 3 GBit AHCI
INTERFACES	
Audio: line-in	
Audio: line-in / microphone	
Audio: line-out	
Front audio: headphone	
Front audio: line-in / microphone	:
USB 2.0 total	12
USB front	2
USB rear	6
USB internal	4
VGA	1
DVI	1
Serial (RS-232)	1 (9pin, 16 byte FIFO, 16550 compatible)
Mouse / Keyboard (PS/2)	2
Ethernet (RJ-45)	1
Parallel	1 (optional) (25pin with EPP and ECP)
eSATA	1 (optional)
Interface Module notes	Anytime USB charge functionality
INPUT DEVICE / COMPONENTS	
	Optical USB wheel mouse
Input devices (optional)	Optical USB/PS2 tilt wheel mouse
DRIVE BAYS	
Drive bays total	3
3.5-inch internal bays	1
3.5-inch external bays	
5.25-inch external bays	1
Drive bay notes	optional external bay as internal 3,5"
SLOTS	
PCI-Express 2.0 x16	1 x (210 mm) low profile
PCI-Express x4 (mech. x8)	1 x (210 mm) low profile
PCI (32-bit / 33 MHz)	2 x (170/ 190 mm) low profile
GRAPHICS ON BOARD	
Graphics brand name	Intel® HD Graphics (integrated in dual-core processors only)
Shared video memory	up to 1759 MB
onarou vidoo illoliloi y	מאָ נס דר סט וויוט

Page 3 / 7

GRAPHICS ON BOARD	05.11-7
Refresh rate 1024 x 768 (recommended / max.)	85 Hz / -
Refresh rate 1280 x 1024 (recommended / max.)	85 Hz / -
Refresh rate 1600 x 1200 (recommended / max.)	85 Hz / -
TFT resolution (VGA)	1360 x 768 pixel 1440 x 900 pixel 1600 x 900 pixel 1680 x 1050 pixel 1920 x 1080 pixel 1920 x 1200 pixel
TFT resolution (DVI)	1360 x 768 pixel 1440 x 900 pixel 1600 x 900 pixel 1680 x 1050 pixel 1920 x 1080 pixel 1920 x 1200 pixel
Graphics features	Dual display support DirectX 10 OpenGL® 2.1
Graphics notes	Graphics controller integrated in dual-core processors. For quad-core processors graphics card is mandatory. Tested resolutions, depending on display type additional resolutions and frequencies possible Shared memory depending on main memory size and operating system Resolution (color depth up to 32 Bit/pixel) For TFT we recommend using 60Hz
ELECTRICAL VALUES	
Power efficiency note	power supply efficiency (at 230V; 20% / 50% / 100% load) : 86% / 88% / 85%)
	0-Watt mode with hard-off switch
Rated voltage range	100 - 240 V
Rated frequency range	50 - 60 Hz
Operating voltage range	90 - 264 V
Operating line frequency range	47 - 63 Hz
Max. output of single power supply	250 W
Power factor correction/active power	active
Monitor outlet	No
POWER CONSUMPTION	
Power consumption note	See white paper Energy Consumption
Link to Energy White Paper	http://docs.ts.fujitsu.com/dl.aspx?id=2983c9fa-1b3d-4225-80bf-1de84d527d29
HEAT DISSIPATION	
Heat dissipation notes	See white paper Energy Consumption
	1.1 65
NOISE FOR STANDARD CONFIGURATION	· · ·
Noise emission Related Processors for noise	According to ISO9296 Intel® Core™ i5-680; Intel® Core™ i7-870 including NVIDIA® Geforce® 9300
Noise Operation mode 1: ODD load	4.5 B / 30 dB(A)
(Blue angel requirement) Noise Operation mode 2: HDD load (Blue angel requirement)	3.8 B / 22 dB(A) ; 3.8 B / 23 dB(A)
Noise Operation mode 3: CPU 90% load (Blue angel requirement)	d 4.0 B / 25 dB(A) ; 5.1 B / 36 dB(A)
Noise Operation mode 4: High load	4.0 B / 25 dB(A) ; 5.1 B / 36 dB(A)
Noise Operation mode 5: Office applications	3.8 B / 22 dB(A) ; 3.8 B / 23 dB(A)
Idle mode (Blue Angel requirement)	3.8 B / 22 dB(A) ; 3.8 B / 23 dB(A)
Noise notes / description	A weighted sound power level Lwad (in B) / workplace related A-weighted sound pressure level LpAm (in dB(A)), Bystander
	position

DIMENSIONS / WEIGHT / ENVIRONME	NTAL
Dimensions (W x D x H)	330 x 405 x 104 mm
Operating position	Vertical / horizontal (optional, feet needed)
Weight	approx. 10 kg
Weight notes	Actual weight may vary depending on configuration
Operating ambient temperature	10 - 35°C
COMPLIANCE	
Product	ESPRIMO E3721
Model	DTL-2942
Germany	Blauer Engel / Blue Angel GS
Europe	CE
USA/Canada	FCC Class B CSA
Global	RoHS (Restriction of hazardous substances) WEEE (Waste electrical and electronical equipment) Microsoft Operating Systems (HCT / HCL entry / WHQL) ENERGY STAR® 5.0 EPEAT® Silver
Compliance link	https://sp.ts.fujitsu.com/sites/certificates/default.aspx
ADDITIONAL SOFTWARE	
Additional software (preinstalled)	Nero Essentials S (burning software)
Additional software (optional)	Recovery DVD for Windows® Drivers & Utilities DVD (DUDVD) CyberLink PowerDVD BD (playback software for Blu-ray Disc™, only with Blu-ray Disc™ drive / Blu-ray playback is not supported under Windows XP if the system runs on Intel onboard graphics) Nero 9 Essentials XL
COMPATIBILITY (REFERENCES)	
	DMI 2.0 PC 2001 WMI 1.5 USB 2.0 SMBIOS
MANAGEABILITY	
Manageability features	DeskUpdate Driver management PXE 2.1 Boot code Wake up from S5 (off mode)
DeskView features	WoL (Wake on LAN)
Manageability link	http://ts.fujitsu.com/manageability http://www.altiris.com/fujitsu
SECURITY	
Physical security	Kensington Lock support Eye for padlock
System security	Boot sector virus protection Write protect option for the Flash EPROM Boot protection for floppy disk / CD drive and write protection for floppy disk drive Control of all USB interfaces
User security	User and supervisor BIOS password Optional: Access protection via external SmartCard reader Optional: Access protection via internal SmartCard reader
PACKAGING INFORMATION	
Packaging dimension	500x290x540 mm
Max. quantity / pallet	24
	1270 g
	200g
	appr. 60 g
Packaging notes	printed user documentation is bleached in chlorine free process
Material - Weight (g) Carton Material - Weight (g) EPS / PS Material - Weight (g) PE Packaging notes	1270 g 200g appr. 60 g

WARRANTY		
Standard Warranty	1 year	
Service level MAINTENANCE AND SUPPORT	Bring-In / On-Site Service (depending on country) SERVICES - THE PERFECT EXTENSION	
Recommended Service	5x9, Response Time: Next Business Day	
Spare Parts availability	5 years	
Service Weblink	http://ts.fuiitsu.com/Supportservice	

Page 6 / 7 http://ts.fujitsu.com/ESPRIMO

FUJITSU PLATFORM SOLUTIONS

In addition to Fujitsu ESPRIMO E3721 E-Star 5.0, Fujitsu provides a range of platform solutions. They combine reliable Fujitsu products with the best in services, know-how and worldwide partnerships.

Dynamic Infrastructures

With the Fujitsu Dynamic Infrastructures approach, Fujitsu offers a full portfolio of IT products, solutions and services, ranging from clients to datacenter solutions, Managed Infrastructure and Infrastructure as-a-Service. How much you benefit from Fujitsu technologies and services depends on the level of cooperation you choose. This takes IT flexibility and efficiency to the next level.

Computing Products

www.fujitsu.com/global/services/computing/

Software

www.fujitsu.com/software/

MORE INFORMATION

Learn more about Fujitsu ESPRIMO E3721 E-Star 5.0, please contact your Fujitsu sales representative or Fujitsu Business partner, or visit our website.

http://ts.fujitsu.com/ESPRIMO

FUJITSU GREEN POLICY INNOVATION

Fujitsu Green Policy Innovation is our worldwide project for reducing burdens on the environment. Using our global know-how, we aim to resolve issues of environmental energy efficiency through IT. Please find further information at http://www.fujitsu.com/global/about/environment/



COPYRIGHTS

All rights reserved, including intellectual property rights. Changes to technical data reserved. Delivery subject to availability. Any liability that the data and illustrations are complete, actual or correct is excluded.

Designations may be trademarks and/or copyrights of the respective manufacturer, the use of which by third parties for their own purposes may infringe the rights of such owner. For further information see http://ts.fujitsu.com/terms_of_use.html

Copyright © Fujitsu Technology Solutions

DISCLAIMER

Technical data are subject to modification and delivery subject to availability. Any liability that the data and illustrations are complete, actual or correct is excluded. Designations may be trademarks and/or copyrights of the respective manufacturer, the use of which by third parties for their own purposes may infringe the rights of such owner

CONTACT

FUJITSU Technology Solutions Website: http://ts.fujitsu.com 2010-10-28 CE-EN